



PICKETS

Certified Tasmanian Plantation Pine

TIMBERLINK. MADE OF TASMANIA.[®]

Timberlink Tasmanian Pickets

Picket fencing is an easy way to add charm and character to your home. We cut our pickets into four different shapes or profiles so you can pick the shape that best suits your home's style, from the more contemporary round profile, to the traditional Windsor.

Picket Profiles

- > Colonial – the classic profile for an Australian picket fence
- > Gothic – cut with a pointed arch, the defining element of Gothic architecture
- > Round – looking like a big paddle pop stick, this is our most simple, modern profile
- > Windsor – more elaborate, heritage look



Suitable Uses

Pickets are treated to an H3 level so are suitable for outdoor above ground applications. They should not be placed in direct contact with the ground.

Treatment

Timberlink Pickets are treated with arsenic free Tanalith-E.

Sustainably Sourced Tasmanian Pine

At Timberlink Bell Bay we manufacture all our pickets from Tasmanian grown plantation pine.

INSTALLATION INFORMATION

Fixings

Hot dip galvanised or stainless-steel corrosion resistant fasteners, fixings and connectors are recommended for use for all outdoor timber projects.

Resealing

All cut ends, notches, rebates and drill holes must be resealed with a suitable resealing product, to ensure a treatment envelope is maintained. We recommend Tanalised[®] Ecoseal.

Painting

Machined to a smooth finish, Timberlink pickets can be stained or painted any colour. As with all outdoor timber, we recommend painting or staining your fence to protect it from weathering. For best results apply a coat of finish to the timber prior to installation and then another to the finished structure, including ends.

Spacing

The spacing of pickets for the Victorian period is usually the same as the width of the picket. Federation period fences have closer spaces between pickets. You can use a picket on its edge as a spacer to ensure the spacing is consistent.

Product Specification

Size (mm)	70 x 19
Lengths (m)	0.9, 1.2, 1.5, 1.8
Profiles	Windsor, Colonial, Round, Gothic
Finish	Machined to smooth finish
Hazard Class	H3 above ground outdoor use
Treatment	Tanalith E
Species	Tasmanian Radiata Pine